

**PER APPARECCHI
A FUNE PASSANTE
FOR MANUAL
WINCHES**


FZ526TK

Zincata EN 10264-2 classe B
Trefoli compattati
Anima polipropilene
Crociata destra
Resistenza 1960 N/mm²
EN 12385-4

Galvanized EN 10264-2 class B
Compacted strands
Polypropylene core
Right Regular Lay
Tensile rope grade 1960 N/mm²
EN 12385-4

CRITERI DI SCARTO ISO 4309 / DISCARD CRITERIA ISO 4309

Diametro fune Rope diameter mm	RCN	Fili portanti esterni Outer load bearing wires n	Max fili rotti su una lunghezza di mm Max breaking wires on length of mm			
			L = 6 x Ø		L = 30 x Ø	
			Strato singolo Single layer	Multistrato Multilayer	Strato singolo Single layer	Multistrato Multilayer
8,4÷16,3	05	130	3	6	5	11



5xK19S+PP
(Ø8,4 - Ø11,5)

5xK26WS+PP
(Ø16,3)

Codice Code	Diametro fune Rope diameter mm	Tolleranza sul diametro Tolerance on diameter mm	Peso per metro Weight for meter kg	Carico rottura minimo MBL	
				kN	kg
FZCIN08,4	8,4	0-0,2	0,25	54,00	5506
FZCIN11,5	11,5	0-0,3	0,48	93,50	9534
FZCIN16,3	16,3	0-0,3	1,01	194,00	19782

