


Campanella semplice AW

AW Master link

- Per imbracature a 1 e 2 bracci.
- 1 and 2 legs chain slings.



Tipo Type	Portata 0°-45° WLL 0°-45° Kg	Per ganci DIN 15401 Fits on single hook acc. to DIN 15401 n°	Dimensioni Dimensions				Peso Weight Kg	Campanella per catena Ø Master link for chain Ø	
			d mm	t mm	w mm	s mm		1 br. 1 leg	2 br. 2 legs
AW 10	1400	1,6	10	80	50	10	0,14	5	5
AW 13	2300	2,5	13	110	60	10	0,34	6+7	6
AW 16	3500	2,5	16	110	60	14	0,53	8	7
AW 18	5000	5	19	135	75	14	0,86	10	8
AW 22	7600	6	23	160	90	17	1,60	13	10
AW 26	10000	8	27	180	100	20	2,46	16	13
AW 32	14000	10	33	200	110	26	4,14	19	16
AW 36	25100	16	36	260	140	29	6,50	22	19
AW 45	30800	25	45	340	180	-	12,82	26	22
AW 50	40000	32	50	350	190	43	16,55	32	26
AW 56	64000	32	56	400	200	-	22,00	-	32
AW 72	85000	50	70	460	250	-	41,50	-	-

Tolleranza secondo norma DIN.
Tolerances according DIN standard.