


## Campanella maggiorata VLW

VLW Oversize master link assembly




VLW 1

Tipo Type	Assemblaggio Consisting of	Portata WLL Kg	Per ganci DIN 15401 Fits on single hook acc. to DIN 15401 n°	Dimensioni Dimensions				Peso Weight Kg
				d mm	e mm	t mm	w mm	
VLW 1-6/7/8	LW 22 + BW 13	2500	25	23	394	340	180	3,4
VLW 1-10	LW 27 + BW 16	4000	25	27	410	340	180	4,8
VLW 1-13	LW 27	6700	25	27	340	340	180	4,4
VLW 1-16	LW 32	10000	25	33	340	340	180	6,7
VLW 1-19/22	LW 40	19000	25	40	340	340	190	10,0

Esempio: la campanella VLW 1-6/7/8 può essere utilizzata per imbragature a 1 braccio con catena diametro 6 mm, 7 mm e 8 mm.

Example: VLW 1-6/7/8 can be used for 1 leg slings with 6 mm, 7 mm and 8 mm chain.



VLW 2/4

Tipo Type	Assemblaggio Consisting of	Portata 0°-45° WLL 0°-45° Kg	Per ganci DIN 15401 Fits on single hook acc. to DIN 15401 n°	Dimensioni Dimensions				Peso Weight Kg
				d mm	e mm	t mm	w mm	
VLW 2-6/7/8 4-6	LW 22 + 2 BW 13	3550	25	23	394	340	180	3,5
VLW 2-10 4-7/8	LW 27 + 2 BW 16	5600	25	27	410	340	180	5,1
VLW 2-13 4-10	LW 32 + 2 BW 20	9500	25	33	425	340	180	8
VLW 2-16 4-13	LW 40 + 2 BW 22	14000	25	40	455	340	180	12,3
VLW 2-19 4-16	LW 40 + 2 BW 26	21200	25	40	480	340	180	13,8

Esempio: la campanella VLW 2-6/7/8 4-6 può essere utilizzata per imbragature a 2 bracci con catena diametro 6 mm, 7 mm e 8 mm e a 4 bracci con catena diametro 6 mm.

Example: VLW 2-6/7/8 4-6 can be used for 6 mm, 7 mm and 8 mm 2 legs slings and 6 mm 4 legs slings chain.