


Catene e accessori Winner Plus - Grado 12

Winner Plus chain and
accessory system in G12

Campanella semplice AS

AS Master link



| Tipo Type | Portata WLL | | Per ganci singoli DIN 15401 For single hooks DIN 15401 | Per ganci doppi DIN 15402 For double hooks DIN 15402 | Dimensioni Dimensions | | | | Peso Weight Kg | Campanella per catena Ø Master link for chain Ø | |
|--------------|----------------|-----------------|---|---|--------------------------|-----|---------|---------|----------------------|--|---------|
| | 0° - 45° kg | 45° - 60° kg | | | n° | n° | d mm | t mm | | w mm | s mm |
| AS 16 | 3350 | 2360 | 2,5 | 4 | 16,5 | 100 | 56 | 12,5 | 0,54 | 7/8 | 7 |
| AS 19 | 5300 | 3750 | 5 | 4 | 19 | 130 | 75 | 14,5 | 0,93 | 10 | 8 |
| AS 23 | 8000 | 5700 | 6 | 6 | 23 | 147 | 84 | 17,5 | 1,5 | 13 | 10 |
| AS 27 | 12500 | 8900 | 10 | 8 | 27 | 168 | 93 | 20,5 | 2,4 | 16 | 13 |
| AS 33 | 17500 | 12500 | 10 | 12 | 33 | 190 | 110 | 25 | 4,2 | - | 16 |
| AS 40* | 26500 | 19000 | 16 | 20 | 40 | 235 | 134 | 30 | 7,4 | - | - |

* AS 40 è prevista per l'uso con campanelle a III e IV bracci (codice prodotto "VS").

* AS 40 is designed for use in master link assemblies for III-leg and IV-leg chain slings (product code "VS").