

Catene Nichel Plated Kito per paranchi manuali

Kito Nickel Plated chains for manual hoists

KITO

CARATTERISTICHE
SPECIFICATION

CATENA "NICKEL PLATED" "NICKEL PLATED" CHAIN

Kito chain is enhanced in corrosive resistance and bending fatigue by nickel electroless-plating on the link chain in substitution to the former zinc electroplated chain. The chart shows Kito nickel plated chain advantages compared to an electro plating chain and a self coloured chain. In detail, the corrosion and wear resistance without lubrication, the bending fatigue and the elongation. Nickel plating process prevents the hydrogen embrittlement risk by generating less hydrogen and eliminating the absorbed hydrogen. Kito load chains are quality class V (G100) according to EN 818-7.

Le catene Kito sono trattate elettroliticamente al nichel e forniscono resistenza alla corrosione e alla fatica decisamente superiori rispetto alle catene elettro-zincate. Il disegno allegato evidenzia le caratteristiche superiori della catena "nichel plated" rispetto ad una catena non trattata o zincata elettroliticamente. In particolare la resistenza alla corrosione e all'usura in assenza di lubrificazione, la resistenza a fatica e l'allungamento. Il trattamento superficiale al nichel ha inoltre eliminato il problema dell'infragilimento da idrogeno che può capitare durante il processo di zincatura elettrolitica.

Le catene Kito sono di classe V (grado 100) in accordo alle norme EN 818-7.

