


Tipo CVL

Finitura: zincatura elettrolitica

CVL Type

Finish: electrolytic galvanized



| Codice Code | Fune Rope | | Dimensioni Dimensions | | | | | | | | Peso 100 pezzi Weight 100 pcs Kg | Coppia serraggio Tightening torque Nm | N° min. morsetti Min. N° of wire rope clips |
|----------------|--------------|-------------|--------------------------|---------|---------|---------|---------|---------|---------|---------|--|---|---|
| | Ø mm | Ø inches | A | B mm | E mm | H mm | I mm | L mm | R mm | S mm | | | |
| ACVL1/8" | 3 | 1/8 | M4 | 3,2 | 12 | 18 | 9 | 20 | 7 | 10 | 1,2 | 1,5 | 3 |
| ACVL3/16" | 5 | 3/16 | M5 | 4 | 13 | 24 | 13 | 24 | 10 | 15 | 2,2 | 3 | 3 |
| ACVL1/4" | 6 | 1/4 | M6 | 5 | 15 | 27 | 15 | 28 | 11 | 16 | 3,5 | 5,2 | 3 |
| ACVL5/16" | 8 | 5/16 | M6 | 5 | 19 | 31 | 17 | 34 | 12 | 18 | 4,4 | 5,2 | 5 |
| ACVL3/8" | 10 | 3/8 | M8 | 6,5 | 22 | 37 | 20 | 42 | 13 | 21 | 7,5 | 12,5 | 5 |
| ACVL7/16" | 11 | 7/16 | M8 | 6,5 | 22 | 41 | 22 | 44 | 14 | 24 | 8,6 | 12,5 | 5 |
| ACVL1/2" | 12-13 | 1/2 | M10 | 8 | 33 | 44 | 25 | 55 | 15 | 26 | 14 | 25 | 5 |
| ACVL9/16" | 14 | 9/16 | M10 | 8 | 33 | 47 | 27 | 57 | 18 | 27 | 15 | 25 | 5 |
| ACVL5/8" | 16 | 5/8 | M10 | 8 | 33 | 51 | 29 | 63 | 20 | 28 | 18 | 25 | 5 |
| ACVL11/16" | 18 | 11/16 | M12 | 10 | 44 | 56 | 34 | 75 | 21 | 32 | 26 | 42 | 5 |
| ACVL3/4" | 20 | 3/4 | M12 | 10 | 44 | 62 | 34 | 75 | 22 | 33 | 30 | 42 | 5 |
| ACVL7/8" | 22 | 7/8 | M12 | 10 | 52 | 65 | 39 | 85 | 25 | 35 | 35 | 42 | 7 |
| ACVL1" | 24-26 | 1 | M14 | 11 | 50 | 72 | 42 | 95 | 27 | 40 | 48 | 67 | 7 |
| ACVL1-1/16" | 28 | 1 1/16 | M14 | 11 | 50 | 75 | 45 | 100 | 30 | 42 | 52 | 67 | 8 |
| ACVL1-1/8" | 30-32 | 1 1/8 | M14 | 11 | 50 | 80 | 47 | 110 | 33 | 44 | 60 | 67 | 8 |
| ACVL1-1/4" | 34-36 | 1 1/4 | M16 | 13 | 55 | 88 | 53 | 120 | 37 | 48 | 80 | 106 | 8 |
| ACVL1-1/2" | 38-40 | 1 1/2 | M16 | 13 | 60 | 98 | 59 | 140 | 40 | 54 | 112 | 106 | 8 |
| ACVL2" | 45-50 | 2 | M20 | 16 | 80 | 120 | 72 | 150 | 57 | 60 | 192 | 206 | 8 |

Non idonei per sollevamento.

Not suitable for lifting purposes.