

Tipo CVL-EN Green Pin®


In accordo a EN 13411-5 tipo B

- Base: acciaio alta resistenza SAE 1045
- Cavallotto: SAE 1015
- Finitura base: zincata a caldo
- Finitura cavallotto: $\geq 1/2''$ zincatura a caldo < $1/2''$ zincatura elettrolitica

CVL-EN Green Pin® Type

According to EN 13411-5 B type

- Bridge: high tensile steel SAE 1045
- U-bolt: SAE 1015
- Base finish: hot dipped galvanized
- U-bolt finish: $\geq 1/2''$ hot dipped galvanized < $1/2''$ electro galvanized



Codice Code	Fune Rope		Dimensioni Dimensions							Peso 100 pezzi Weight 100 pcs Kg	Coppia serraggio Tightening torque Nm	N° min. morsetti Min. N° of wire rope clips
	Ø mm	Ø inches	a mm	b mm	c mm	d mm	e mm	f mm	g mm			
ACVLVB3/16"	5	3/16	6	31	15	13	29	24	13	7	10,2	2
ACVLVB1/4"	6-7	1/4	8	34	19	13	37	30	18	8	20,3	2
ACVLVB5/16"	8	5/16	10	45	22	19	43	33	19	13	40,7	3
ACVLVB3/8"	9-10	3/8	11	49	26	19	49	42	25	19	61	3
ACVLVB7/16"	11	7/16	12	60	30	25	58	46	26	33	88	3
ACVLVB1/2"	12-13	1/2	13	61	30	25	58	48	31	34	88	3
ACVLVB9/16"	14-15	9/16	14	72	33	32	63	52	31	45	129	3
ACVLVB5/8"	16	5/8	14	74	33	32	64	54	36	45	129	3
ACVLVB3/4"	18-20	3/4	16	86	38	37	72	57	38	68	176	4
ACVLVB7/8"	22	7/8	19	98	45	41	80	62	40	108	305	4
ACVLVB1"	24-26	1	19	108	48	46	88	67	47	113	305	5
ACVLVB1-1/8"	28-30	1 1/8	19	117	51	51	91	73	48	140	305	6
ACVLVB1-1/4"	32-34	1 1/4	22	130	59	54	105	79	56	207	488	7
ACVLVB1-3/8"	36	1 3/8	22	140	60	59	108	79	58	234	488	7
ACVLVB1-1/2"	38-40	1 1/2	22	147	66	60	112	85	64	254	488	8
ACVLVB1-5/8"	42	1 5/8	25	161	70	67	121	92	67	329	583	8
ACVLVB1-3/4"	44-46	1 3/4	29	174	78	70	134	97	76	441	800	8
ACVLVB2"	48-52	2	32	195	86	78	150	113	85	603	1017	8
ACVLVB2-1/4"	56-58	2 1/4	32	213	98	81	162	116	100	707	1017	8
ACVLVB2-1/2"	62-65	2 1/2	32	227	105	87	168	119	113	806	1017	9
ACVLVB2-3/4"	68-72	2 3/4	32	243	112	91	174	127	124	1000	1017	10
ACVLVB3"	75-78	3	38	271	121	98	194	135	136	1472	1627	10

Non idonei per sollevamento.
Not suitable for lifting purposes.