

Tipo KSB

KSB type

- Screw clamps suitable as temporary lifting points or for lifting and transporting steel beams.
- Suitable for HE or IPE beams with dimensions as shown below.
- The clamp must be fixed to the beam centrally above the load's center of gravity. Inclined pulls are not permitted.
- Safety factor 4.
- Morse a vite idonee come punto di sospensione temporaneo per paranchi e per il sollevamento ed il trasporto di travi metalliche.
- Idonee per travi HE o IPE con dimensioni come da tabella.
- La morsa deve essere posizionata in asse con il baricentro del carico. Non sono permessi tiri obliqui.
- Coefficiente di sicurezza 4.

Tipo Type	Portata WLL t	Luce di presa Jaw opening A mm	Dimensioni Dimensions										Peso Weight Kg
			A max mm	B min mm	B max mm	C mm	D mm	E mm	F min mm	F max mm	G min mm	H mm	
KSB - 1	1	80-240	270	183	370	94	4	198	100	154	22	20	3,5
KSB - 2	2	80-240	270	183	370	102	6	198	100	154	22	20	4,5
KSB - 3	3	90-330	355	243	500	132	8	263	148	219	46	22	9,5
KSB - 5	5	90-330	355	243	500	142	10	263	148	219	43	28	11
KSB - 10	10	90-350	364	269	521	180	12	285	165	239	51	38	16

