


Complessivo ad un braccio KMGW 1

KMGW 1 Single leg clevis master set




Tipo Type	Portata WLL Kg	Per catena For chain Ø	Per ganci DIN 15401 Fits on single hook acc. to DIN 15401 n°	Dimensioni Dimensions				Peso Weight Kg
				d mm	e mm	t mm	w mm	
KMGW 1-6*	1400	6	4	14	151	120	70	0,63
KMGW 1-7	1900	7	4	14	163	120	70	0,65
KMGW 1-8	2500	8	5	16	183	140	80	0,91
KMGW 1-10	4000	10	6	19	211	160	95	1,53
KMGW 1-13	6700	13	10	23	233	170	105	2,58
KMGW 1-16	10000	16	10	27	264	190	110	4,14
KMGW 1-19	14000	19	12	33	324	230	130	7,11
KMGW 1-22	19000	22	20	38	377	275	150	11,43

* Idoneo anche per catena da 5 mm, con portata ridotta in accordo.

* May also be used with a 5 mm chain, if load capacity is adjusted accordingly.

Complessivo a due bracci KMGW 2

KMGW 2 Two legs clevis master set




Tipo Type	Portata 0°-45°/45°-60° WLL 0°-45°/45°-60° Kg	Per catena For chain Ø	Per ganci DIN 15401 Fits on single hook acc. to DIN 15401 n°	Dimensioni Dimensions				Peso Weight Kg
				d mm	e mm	t mm	w mm	
KMGW 2-6*	2000 / 1400	6	4	14	151	120	70	0,69
KMGW 2-7	2650 / 1900	7	5	16	183	140	80	1,13
KMGW 2-8	3550 / 2500	8	6	19	203	160	95	1,58
KMGW 2-10	5600 / 4000	10	10	23	221	170	105	2,54
KMGW 2-13	9500 / 6700	13	10	27	253	190	110	4,32
KMGW 2-16	14000 / 10000	16	12	33	304	230	130	8,47
KMGW 2-19	20000 / 14000	19	20	36	369	275	150	12,14
KAGW 2-22	26500 / 19000	22	25	45	442	340	180	21,51

* Idoneo anche per catena da 5 mm, con portata ridotta in accordo.

* May also be used with a 5 mm chain, if load capacity is adjusted accordingly.

Complessivo a quattro bracci KMGW 4

KMGW 4 Four legs clevis master set



Tipo Type	Portata 0°-45°/45°-60° WLL 0°-45°/45°-60° Kg	Per catena For chain Ø	Per ganci DIN 15401 Fits on single hook acc. to DIN 15401 n°	Dimensioni Dimensions				Peso Weight Kg
				d mm	e mm	t mm	w mm	
KMGW 4-6*	3000 / 2120	6	6	19	245	160	95	1,94
KMGW 4-7	4000 / 2800	7	10	23	283	170	105	3,30
KMGW 4-8	5300 / 3750	8	10	23	283	170	105	3,36
KMGW 4-10	8000 / 6000	10	10	27	326	190	110	5,44
KMGW 4-13	14000 / 10000	13	12	33	408	230	130	11,15
KMGW 4-16	21200 / 15000	16	20	38	489	275	150	11,67
KMGW 4-19	30000 / 21200	19	50	56	594	350	250	37,60
KMGW 4-22	40000 / 28000	22	50	56	622	350	250	46,00

* Idoneo anche per catena da 5 mm, con portata ridotta in accordo.

* May also be used with a 5 mm chain, if load capacity is adjusted accordingly.